



WWW.FYICHINA.COM.CN

FANYUAN INSTRUMENT (HF) CO., LTD.
DOWELL SCIENCE & TECHNOLOGY (HK) CO., LTD.
ADD: ROOM 1405#, TIANYI INTERNATIONAL BUILDING, NO.19
TIANBO ROAD, HI-TECH DISTRICT, HEFEI, CHINA
POSTAL CODE: 230088
TEL: +86-551-68105003
FAX: +86-551-65232507
EMAIL: SALES@HKDOWELL.COM

DW1330D DRY SIEVE TESTER



Sieve



FANYUAN INSTRUMENT (HF) CO., LTD.
DOWELL SCIENCE & TECHNOLOGY (HK) CO., LTD.
ADD: ROOM 1405#, TIANYI INTERNATIONAL BUILDING, NO.19
TIANBO ROAD, HI-TECH DISTRICT, HEFEI, CHINA
POSTAL CODE: 230088
TEL: +86-551-68105003
FAX: +86-551-65232507
EMAIL: SALES@HKDOWELL.COM

MODEL NO.:

DW1330D

APPLICATION:

DW1330D DRY SIEVE TESTER is used to determine the apparent/equivalent opening size of a geotextile by sieving sized glass beads through the geotextile, using the dry-sieve principle. A geotextile specimen is placed in a sieve frame and sized glass beads are placed on the geotextile surface. The geotextile and frame are shaken laterally so that the jarring motor will induce the beads to pass through the test specimen. The procedure is repeated on the same specimen with various sized glass beads until its apparent opening size has been determined. The apparent opening size (O_{90}/O_{95}) of the geotextile corresponds to a specified size of graded glass beads passed (d_{90}/d_{95}).

RELATED STANDARDS:

STANDARDS	ASTM D4751	GB/T 14799
-----------	------------	------------

Note: this tester can conform to but not limit to all the standards above, for more standards conformance, please contact us.

FEATURES:

- Mechanical sieve shaker vibrates smoothly and efficiently;
- Two vibration mode: lateral and vertical;
- Vibrating time is settable;
- Digital display of time.

KEY SPECIFICATION:

- | | |
|---------------------------------|-----------|
| ● Inner diameter of sieves | Φ200mm |
| ● Sieve material | Aluminium |
| ● Number of sieves | 5 |
| ● Superimposed height of sieves | 400mm |
| ● Amplitude | 8mm |



WWW.FYICHINA.COM.CN

FANYUAN INSTRUMENT (HF) CO., LTD.
DOWELL SCIENCE & TECHNOLOGY (HK) CO., LTD.
ADD: ROOM 1405#, TIANYI INTERNATIONAL BUILDING, NO.19
TIANBO ROAD, HI-TECH DISTRICT, HEFEI, CHINA
POSTAL CODE: 230088
TEL: +86-551-68105003
FAX: +86-551-65232507
EMAIL: SALES@HKDOWELL.COM

-
- Timer range 0~99min59s
 - Lateral vibration frequency 221times/min
 - Vertical vibration frequency 147times/min
 - Radius of gyration 12.5mm
 - Power supply AC380V, 50Hz, 3phase
 - Package dimensions 720×440×1,140mm (L×W×H)
 - Gross weight 157kg

STANDARD CONFIGURATION:

No.	Item	Quantity
1.	Main machine	1 set
2.	Control box	1 set
3.	Standard sieves (installed on main machine)	5 pcs
4.	Pans (installed on main machine)	5 pcs

OPTIONAL ACCESSORY:

No.	Item
1.	Spherical glass beads