

#### FANYUAN INSTRUMENT (HF) CO., LTD. DOWELL SCIENCE & TECHNOLOGY (HK) CO., LTD.

ADD: ROOM 1405#, TIANYI INTERNATIONAL BUILDING, NO.19 TIANBO ROAD, HI-TECH DISTRICT, HEFEI, CHINA

> POSTAL CODE: 230088 TEL: +86-551-68105003 FAX: +86-551-65232507

EMAIL: SALES@HKDOWELL.COM

# YG026PC ELECTRONIC STRENGTH TESTER



### **MODEL NO.:**

#### YG026PC

### **APPLICATION:**

YG026PC Electronic Strength Tester is used to determine the mechanical property of woven fabric, non-woven fabric, knitted fabric, inluding tensile, tearing, seam slippage, elastic recovery, etc.



# FANYUAN INSTRUMENT (HF) CO., LTD. DOWELL SCIENCE & TECHNOLOGY (HK) CO., LTD.

ADD: ROOM 1405#, TIANYI INTERNATIONAL BUILDING, NO.19
TIANBO ROAD, HI-TECH DISTRICT, HEFEI, CHINA

POSTAL CODE: 230088 TEL: +86-551-68105003 FAX: +86-551-65232507

EMAIL: SALES@HKDOWELL.COM

### **RELATED STANDARDS:**

Tensile	ISO 9073-3, 13934-1/2; ASTM D461, 5034, 5035; JIS L1096
Tearing	ISO 13937-2/3/4; ASTM D2261
Seam slippage	ISO 13936-1/2; ASTM D434, 1683

Note: this tester can conform to but not limit to the standards above, for more standards conformance, please contact us.

#### **FEATURES**:

- More sensor range, the device can automatically identify, the operation is easy, simply replace the sensor and clamp.
- Multifunction: Tensile, tearing, seam slippage test are built-in the software, it can be customized according to customer's requirement.
- Multiple standards: There are some standard methods built-in the software, the customer can select or customize it.
- Menu applications: The software is divided into several modules according to functions, with simple interface and simple operation. The software is equipped with printing, exporting, real-time curve display and other functions.
- Imported components: Fast reaction speed, high control accuracy, providing unparalleled stability and accuracy.

#### **KEY SPECIFICATION:**

• Strength capacity 12kg, 50kg, 300kg, 500kg, 1,000kg

● Load range 0.4-100%FS

• Accuracy  $\pm 0.5\%$  FS

• Speed 1-1,000mm/min

• Column space 383mm

• Travel Max. 730mm

• Displacement accuracy 0.5μm

Communication Interface Ethernet



#### FANYUAN INSTRUMENT (HF) CO., LTD. DOWELL SCIENCE & TECHNOLOGY (HK) CO., LTD.

ADD: ROOM 1405#, TIANYI INTERNATIONAL BUILDING, NO.19
TIANBO ROAD, HI-TECH DISTRICT, HEFEI, CHINA

POSTAL CODE: 230088 TEL: +86-551-68105003 FAX: +86-551-65232507

EMAIL: SALES@HKDOWELL.COM

Motor Panasonic servo motor

• Power supply AC220V, 50Hz

• Dimensions 770\*640\*1,530mm (L\*W\*H)

• Net weight 160kg

## **STANDARD CONFIGURATION:**

No.	Item	Quantity
1.	Main machine	1 set
2.	Clamp	1 pair
3.	Software	1 disc

### **OPTIONAL ACCESSORIES:**

No.	Item
1.	PC
2.	Printer